



[ELK-P112K pictured]

## **ELK-P112 / P112K 12V Power Supply in Can**

The ELK-P112 is a high quality 12 VDC Power Supply complete with a metal can enclosure and plug-in transformer. It provides 1 Amp of continuous current and features automatic resetting “fuseless” overload protection and diagnostic LED indicators. The “K” suffix specifies the addition of a 12V, 5.0Ah rechargeable battery.

- Size: 7.5" W x 12.5" H x 3.75" D

## **ELK-P124 / P124K 24V Power Supply in Can**

The ELK-P124 is a high quality 24 VDC Power Supply complete with a metal can enclosure and plug-in transformer. It provides .8 Amps of continuous current and features automatic resetting “fuseless” overload protection and diagnostic LED indicators. The “K” suffix specifies the addition of two (2) 12V, 5.0Ah rechargeable batteries.

- Size: 7.5" W x 12.5" H x 3.75" D



## **ELK-P1216 Plug-in Switching Power Supply**

An all purpose 12 Volt DC Plug-In Switching Power Supply ideal for alarm, access control, and CCTV applications. It plugs into 100 to 120 volts A.C., and supplies 1.6 Amps of regulated 12 VDC from a 2.1mm power plug.

- DC Output Voltage: 12 Volts DC
- Current Rating: 1.6 Amps
- AC Input Voltage Range: 100-120 @ 47-63 Hz
- Size: 3" H x 2" W x 1.75" D



[ELK-P412K pictured]

## **ELK-P412/P412K 4 Amp 12V Power Supply/Can**

A high current power supply packed complete with metal can, AC power cord, and a power distribution board. It features three (3) DC power outputs, each with automatic resetting overload protection and power indicator. It also has a master On/Off switch and built-in low battery cut-off to protect the backup battery from deep discharging when AC power is off for a long time. The “K” suffix specifies the addition of a 12V, 8.0Ah rechargeable battery.

- Size: 7.5" W x 12.5" H x 3.75" D